

# Waterproof Multi-range Conductivity Meter w/ built-in temperature sensor

## HI 8733



### Description :

HI 8633 and HI 8733 have been designed specifically for use in areas of production and quality control. It is often necessary to test samples with different concentrations ranging from deionized water to brine.

The amperometric system would require constant recalibration and probe changes, thus making the measurement process very time consuming and unreliable. To solve this problem, the HI 8633 has been developed, which uses a 4-ring potentiometric probe. The rugged probe is made of PVC - ideal for indoor, as well as outdoor measurements.

By using one point calibration, it is now possible to obtain accurate readings across a very wide range, from 0.1 to 199900  $\mu\text{S}/\text{cm}$ .

If temperature of the solution fluctuates, HI 8733, with a built-in temperature sensor and Automatic Temperature Compensation, is the perfect instrument.

As an accessory, HI 721313 is available. The kit includes a rugged carrying case with a beaker, a calibration screwdriver and standardizing solution at 12880  $\mu\text{S}/\text{cm}$ .

### Specification :

<b>Range</b>	<b>: 0.0 to 199.9 <math>\mu\text{S}/\text{cm}</math>; 0 to 1999 <math>\mu\text{S}/\text{cm}</math>; 0.00 to 19.99 <math>\text{mS}/\text{cm}</math>; 0.0 to 199.9 <math>\text{mS}/\text{cm}</math></b>
<b>Resolution</b>	<b>: 0.1 <math>\mu\text{S}/\text{cm}</math>; 1 <math>\mu\text{S}/\text{cm}</math>; 0.01 <math>\text{mS}/\text{cm}</math>; 0.1 <math>\text{mS}/\text{cm}</math></b>
<b>Accuracy</b>	<b>: <math>\pm 1\%</math> F.S. (excluding probe error)</b>
<b>Calibration</b>	<b>: manual, 1 point</b>
<b>Temperature Compensation</b>	<b>: automatic, 0 to 50°C (32 to 122°F) with <math>\beta</math> adjustable from 0 to 2.5%/°C</b>
<b>Probe</b>	<b>: HI 76302W, ATC, with 1 m (3.3') cable (included)</b>
<b>Battery Type / Life</b>	<b>: 1 x 9V / approx. 100 hours of continuous use</b>
<b>Environment</b>	<b>: 0 to 50°C (32 to 122°F); RH max 100%</b>
<b>Dimensions</b>	<b>: 164 x 76 x 45 mm (6.4 x 3.0 x 1.8")</b>
<b>Weight</b>	<b>: 250 g (8.8 oz.)</b>