

# Infrared Thermometer

## IRX-63 /IRX-64/IRX-65 /IRX-66



### Features:

- °C/°F Selection
- DUAL Laser Target Pointer Selection
- Automatic Data Hold Function
- Auto Power OFF
- White Backlit LCD Display
- Over range indication
- Max. Min. DIF. AVG record
- High and Low Alarm
- Trigger Lock
- Adjustable Emissivity
- Type K temperature measurements



### Technical Data :

| Model               |         | IRX-63                | IRX-64         | IRX-65         | IRX-66         |
|---------------------|---------|-----------------------|----------------|----------------|----------------|
| Range               | IR      | -50°C ~ 850°C         | -50°C ~ 1050°C | -50°C ~ 1250°C | -50°C ~ 1550°C |
|                     |         | -58°F ~ 1472°F        | -58°F ~ 1922°F | -58°F ~ 2282°F | -58°F ~ 2822°F |
|                     | Contact | -50°C ~ 1370°C        |                |                |                |
|                     |         | -58°F ~ 2498°F        |                |                |                |
| IR Temp. Resolution |         | 0.1°C / °F            |                |                |                |
| Basic Accuracy      |         | ±1.5% of reading      |                |                |                |
| Emissivity          |         | Adjustable 0.10 ~ 1.0 |                |                |                |
| Optical Resolution  |         | 30 : 1                |                |                |                |

- **Standard Accessories** : Carrying case, Manual, type K Bead Probe, Carry Hook
- **Dimension** : 192(H) x 83(W) x 95(D)mm